



Hole Opener - Lo Torque

Operating Specifications

				CUTTER STYLES			
BODY TYPE	PILOT HOLE		OPENING SIZE	MILL TOOTH		TCI	
				WOB lb (000's)	RPM	WOB lb (000's)	RPM
LT-2	2.1/2"		6"	3-7	50-80	3-7	30-60
LT-4	4.1/2"		8"	8-10	50-90	10-12	40-80
			10"	8-10	50-90	10-12	40-80
			12"	8-10	50-90	10-12	40-80
LT-6	6.1/2"		12"	10-15	40-100	15-20	35-90
			14"	10-15	40-100	15-20	35-90
			16"	10-15	40-100	15-20	35-80
LT-8	8.1/2"	A	16"	15-20	40-100	20-40	35-90
		B	18"	15-20	40-90	20-40	35-80
		C	20"	15-20	40-80	20-40	35-80
		D	22"	15-20	40-75	20-40	35-70
LT-16	16"	A	24"	15-25	40-75	20-40	35-70
		B	26"	15-25	40-75	20-40	35-70
		C	28"	15-25	40-75	20-40	35-70
		D	30"	15-25	40-65	20-40	35-60
LT-24	24"	A	32"	15-30	35-60	20-50	35-55
		B	34"	15-30	35-60	20-50	35-55
		C	36"	15-30	35-60	20-50	35-55
		D	38"	15-30	35-60	20-50	35-55
LT-32	32"	A	40"	15-30	35-55	20-50	35-50
		B	42"	15-30	35-55	20-50	35-50
		C	44"	15-30	35-55	20-50	35-50
		D	46"	15-30	35-55	20-50	35-50
LT-40	40"	A	48"	15-30	35-50	20-50	30-45
		B	50"	15-30	35-50	20-50	30-45
		C	52"	15-30	35-50	20-50	30-45
		D	54"	15-30	35-50	20-50	30-45
LT-48	48"	A	56"	15-35	35-45	20-60	25-40
		B	58"	15-35	35-45	20-60	25-40
		C	60"	15-35	35-45	20-60	25-40
		D	62"	15-35	35-45	20-60	25-40

Prime Horizontal B.V. ▪ Zuiderkade 25a ▪ 1948 NG Beverwijk ▪ The Netherlands

P: +31 251 271 790 ▪ F: +31 251 271 064 ▪ E: office@primehorizontal.com